

# KT&C EZHD-TVI Cameras

## Feature Filled - In-Stock - Low Cost



Series	B1-Cameras		C1-Cameras			c2-EXIR Cameras		
Model	KEZ-b1BR*IR	KEZ-b1TR*IR	KEZ-c1TR28V12XIR	KEZ-c1DI28V12IR	KEZ-c1BR28V12IR	KEZ-c2TR28V12XIR	KEZ-c2BR28V12XIR	KEZ-c2BR*XIR
Sensor	720p with 0.01 Lux		720p with 0.001 Lux			1080p with 0.01 Lux		
Day/Night	True D/N		True D/N			True D/N		
CVBS	n/a		CVBS Video Out*			CVBS Video Out**		
Wide Dynamic Range	n/a		Digital WDR			120dB True WDR**		
Digital Zoom	n/a		Digital Zoom			Digital Zoom + Smart Digital Zoom		
DNR	2D DNR		3D DNR			3D DNR		
DSS	n/a		DSS			DSS		
Smart IR Range	66' IR		164' EXIR	100' IR	131' IR	164' EXIR		262' Dual EXIR
Up The Cable (UTC) OSD Control	n/a		UTC/OSD	UTC/OSD		UTC/OSD	UTC/OSD	UTC/OSD
In-Camera Joystick Local OSD Control	n/a		n/a	Joystick/OSD		n/a	Joystick/OSD	n/a
Lens	2.8 or 3.6mm		2.8-12mm			2.8-12mm	2.8-12mm	3.6, 6, 12mm
Video Test Point	n/a		n/a	Video Test Point		n/a	Video Test Point	n/a
Weather Rating	IP66 Weather Resistant		IP66 Weather Resistant	Indoor	IP66 Weather Resistant	IP66 Weather Resistant		
Temp Rating	-40° to +140° F		-4° to +140° F			-4° to +140° F		
Easy Twist Mount	n/a		n/a	Easy Twist Mount	n/a	n/a	n/a	n/a
Voltage	12VDC		12VDC			12VDC	12VDC/24VAC	12VDC



Series	c2DI-Cameras		c2DR-Cameras	
Model	KEZ-c2DI28V12W KEZ-c2DI28V12B	KEZ-c2DI28V12IRW KEZ-c2DI28V12IRB	KEZ-c2DR28V12	KEZ-c2DR28V12IR
Sensor	1080p with 0.5 Lux		1080p with 0.5 Lux	
Day/Night	Digital D/N	True D/N	Digital D/N	True D/N
CVBS	CVBS Video Out		CVBS Video Out	
Wide Dynamic Range	Digital WDR		Digital WDR	
Digital Zoom	Digital Zoom		Digital Zoom	
DNR	3D DNR		3D DNR	
DSS	DSS		DSS	
Smart IR Range	n/a	66' IR	n/a	66' IR
Up The Cable (UTC) OSD Control	UTC/OSD		UTC/OSD	
In-Camera Joystick Local OSD Control	Joystick/OSD		Joystick/OSD	
Lens	2.8-12mm		2.8-12mm	
Video Test Point	Video Test Point		Video Test Point	
Weather Rating	Indoor		IP68 Water Resistant	
Temp Rating	-14° to +122° F		-40° to +140° F	
Easy Twist Mount	Easy Twist Mount		n/a	
Voltage	12VDC/24VAC		12VDC/24VAC	

\*HD video output is disabled while CVBS output is active.

\*\*CVBS output and digital zoom are disabled when True WDR is active; where full time CVBS output is desired, Digital WDR is an OSD menu option.

KT&C America, Inc. reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

New Jersey Office  
40 Lane Road 1st Floor  
Fairfield, NJ 07004  
T: 973-276-0118 | F: 973-276-0116

New York Office  
200 Pkwy Drive South Suite 200  
Hauppauge, NY 11788  
T: 631-864-0118 | F: 631-864-0116

California Office  
3240 Wilshire Blvd Suite 501  
Los Angeles, CA 90010  
T: 213-381-0061 | F: 213-381-0064

www.ktncusa.com